

Hydraulic Diaphragm Metering Pump Orlita® Evolution 4

Maximum process reliability and flexibility.



Capacity range of single pump: 55 – 7,400 l/h, 400 – 10 bar

The Orlita® Evolution hydraulic diaphragm metering pump range of EF1a, EF2a, EF3a and EF4a form an integrated product range with stroke lengths of 15 to 40 mm. This covers the capacity range of 3 to 7,400 l/h at 400 – 10 bar. A wide range of drive

versions is available, including some with ATEX certification for use in Zone 1 or Zone 2 areas at risk from explosion. The Orlita® Evolution product range is designed to comply with API 675.

Your benefits

Maximum process reliability:

- PTFE multi-layer diaphragm with integral diaphragm rupture warning system
- Integral hydraulic relief valve
- The new diaphragm position control protects against operating faults (e. g. no damage in the event of a blockage on the suction or discharge side)
- Metering reproducibility is better than $\pm 1\%$ within the 10 – 100% stroke length range under defined conditions and with correct installation

- Continuous bleeding of the hydraulic oil chamber ensures reliable operation

Excellent flexibility:

- The modular compact construction with single and multiple pump versions allows for a wide range of applications, also for multiple pump systems, whereas up to 5 metering units, even with different pump capacities, can be combined.
- 7 different gear ratios are available
- Power end configuration ideal for installation in any position (vertical or horizontal)
- Customised designs are available on request

Field of application

- Oil and gas industry
- Volume-proportional metering of chemicals/ additives in the treatment of boiler feed water
- Metering of reactants and catalysts in the chemical industry

- Level-dependent metering of auxiliary agents in industrial production engineering, for instance hot wax metering in the production of adhesive strips

Hydraulic Diaphragm Metering Pump Orlita® Evolution 4

Maximum process reliability and flexibility.

Technical data for EF4a single pump 50 Hz SST

Plunger Ø mm	Stroke volume ml/stroke	Theoretical pump capacity in l/h at strokes/min (50 Hz)							Max. pressure bar	Efficiency at 100% press.	Efficiency at 50% press.	Standard type of valve
		73 [2] l/h	97 [3] l/h	116 [4] l/h	145 [5] l/h	165 [6] l/h	181 [7] l/h	201 [8] l/h				
22	15.21	67	89	106	132	151	165	183	400	0.71	0.84	DN 16
25	19.63	86	114	137	171	194	213	237	320	0.72	0.85	DN 16
30	28.27	124	165	197	246	280	307	341	222	0.73	0.85	DN 16
34	36.32	159	211	253	316	360	394	438	172	0.80	0.87	DN 16
38	45.36	199	264	316	395	449	493	547	138	0.86	0.90	DN 20
44	60.82	266	354	423	529	602	661	733	103	0.90	0.92	DN 20
50	78.54	344	457	547	683	778	853	947	80	0.93	0.94	DN 32
60	113.10	495	658	787	984	1,120	1,228	1,364	55	0.94	0.95	DN 32
70	153.94	674	896	1,071	1,339	1,524	1,672	1,857	40	0.94	0.95	DN 40
75	176.71	774	1,028	1,230	1,537	1,749	1,919	2,131	35	0.95	0.96	DN 40
86	232.35	1,018	1,352	1,617	2,021	2,300	2,523	2,802	27	0.96	0.97	DN 50
90	254.47	1,115	1,481	1,771	2,214	2,519	2,764	3,069	24	0.96	0.97	DN 50
100	314.16	1,376	1,828	2,187	2,733	3,110	3,412	3,789	20	0.97	0.98	DN 50
110	380.13	1,665	2,212	2,646	3,307	3,763	4,128	4,584	16	0.98	0.98	DN 50
115	415.48	1,820	2,418	2,892	3,615	4,113	4,512	5,011	15	0.98	0.99	DN 65
130	530.93	2,325	3,090	3,695	4,619	5,256	5,766	6,403	12	0.99	0.99	DN 65
140	615.75	2,697	3,584	4,286	5,357	6,096	6,687	7,426	10	0.99	0.99	DN 65

Technical data for EF4a single pump 60 Hz SST

Plunger Ø mm	Stroke volume ml/stroke	Theoretical pump capacity in l/h at strokes/min (60 Hz)					Max. pressure bar	Efficiency at 100% press.	Efficiency at 50% press.	Standard type of valve
		88 [2] l/h	117 [3] l/h	140 [4] l/h	175 [5] l/h	199 [6] l/h				
22	15.21	80	107	128	160	182	400	0.71	0.84	DN 16
25	19.63	104	138	165	206	234	320	0.72	0.85	DN 16
30	28.27	149	198	237	297	337	222	0.73	0.85	DN 16
34	36.32	192	255	305	381	434	172	0.80	0.87	DN 16
38	45.36	240	318	381	476	542	138	0.86	0.90	DN 20
44	60.82	321	427	511	639	726	103	0.90	0.92	DN 20
50	78.54	415	551	660	825	938	80	0.93	0.94	DN 32
60	113.10	597	794	950	1,188	1,350	55	0.94	0.95	DN 32
70	153.94	813	1,081	1,293	1,616	1,838	40	0.94	0.95	DN 40
75	176.71	933	1,241	1,484	1,855	2,110	35	0.95	0.96	DN 40
86	232.35	1,227	1,631	1,952	2,440	2,774	27	0.96	0.97	DN 50
90	254.47	1,344	1,786	2,138	2,671	3,038	24	0.96	0.97	DN 50
100	314.16	1,659	2,205	2,639	3,299	3,751	20	0.97	0.98	DN 50
110	380.13	2,007	2,669	3,193	3,991	4,539	16	0.98	0.98	DN 50
115	415.48	2,194	2,917	3,490	4,363	4,961	15	0.98	0.99	DN 65
130	530.93	2,803	3,727	4,460	5,575	6,339	12	0.99	0.99	DN 65
140	615.75	3,251	4,323	5,172	6,465	7,352	10	0.99	0.99	DN 65

Note: Abridged presentation of our complete product range. Additional plunger diameters (22 – 140 mm) on request.

Materials in Contact With the Medium

Dosing head complete

Dosing head	Diaphragm retaining screw	Diaphragm
Stainless steel 1.4404	Stainless steel 1.4462	PTFE multi-layer diaphragm

Plate valve

	Suction/ pressure connector	Valve/ head seal	Valve plate	Valve seat	Valve housing
DN 16 – DN 65	Stainless steel 1.4404	Stainless steel 1.4571	Stainless steel 1.4462	Stainless steel 1.4404	Stainless steel 1.4404

SYDNEY OFFICE

Unit 4, 4 Narabang Way,
BELROSE NSW 2085
P 02 9450 0995 F 02 9450 0996
sales@prominentfluid.com.au

QUEENSLAND OFFICE

Unit 1, 68 Murdoch Circuit,
ACACIA RIDGE QLD 4110
P 07 3213 1900 F 07 3272 0445
pfcqld@prominentfluid.com.au

VICTORIA OFFICE

Unit 1/21-22 National Drive
HALLAM VIC 3803
P 03 8795 7430 F 03 8975 7431
pfcvic@prominentfluid.com.au

WESTERN AUSTRALIA OFFICE

Office 11, 34 Welshpool Road
Welshpool WA 6106
E: pfcwa@prominentfluid.com.au