

Chlorine Drum Vacuum Regulator Lifting Device

VRL-900

Prominent can now supply a lifting system for placing Vacuum regulators on to 920kg Chlorine drums.

This floor mounted VRL-900 allows the Vacuum Regulator to be easily removed from the chlorine drum outlet valve and replaced on a new drum outlet valve.

The VRL-900 is adjustable for height as well as horizontal positioning with limited rotation to ensure connection to alternate drums and drum valve position.

The VRL-900 is suitable for drums floor mounted or on scales, an is daptable to trolley mounted drums.

The VRL-900 is especially useful when a Proguard (automatic valve closing system) is used due to the extra weight.

The VRL-900 provides support for the Vacuum Regulator during the change over from drum to drum. It also reduces possible operator contact with the drip leg heater. It's designed to allow the Vacuum Regulator to be removed vertically at any time without restriction.

Note: Consideration must be given to ensure that the unit does not restrict the designated walkway.

Model VRL-900

PA24003194

Additional Bracket for Trolley Mount Systems

A240E3204





hydro Gas Chlorinator

Part No: Bottle & Drum Scales

Single Cylinder scales PA24003377

Dual Cylinder scales PA24003360

El1000 Single Chlorine Drum Scale PA24003382

with Digital Alarm and 4-20mA out

El2000 Dual Chlorine Drum Scale PA24003383
with Digital Alarm and 4-20mA out

Trolley & Single Drum Scale & El1000 control unit with Digital Alarm and 4-20mA out


Trolley only for Single Drum (excluding Base - Single Drum only) Note: advise direction of wheels in relation to scale)


For other options contact Sydney Office.

Safety Chains


Safety Chains & Brackets Dual Cylinder

PA31001936





PA24002518 Single Drum Scale & Control Unit (Digital) with alarm & 4-20 mA



PA24022518
Twin Drum Scale &
Control Unit (Digital)
with alarm & 4-20 mA

hydro Gas Chlorinator Accessories

Pressure Connections:		Part No:	
Auxiliary Cylinder Valve, 3/4" inlet and outlet.		IVH-100-500	
Flexible Connection cad. plated annealed copper with 3/4" unions,			
(W & T type drum connection).		FX-06	
1.8m length TON 1.0m length Bottle		FX-04	
Superior Chlorine Valve, for horizontal header mounting.		1214-B1	
/ertical Headers:			
/ertical Wall Header, painted steel c/w drip leg with 3/4" flat face co	nnections & Heater		
VB: top connection for optional pressure gauge, suitable for:	1 x Cylinder	PA24002412	
	2 x Cylinder	PA24002413	
Adaptor 3/4" BSPP male to 5/8" UNF male, plated brass.	3 x Cylinder	PA24002414 A24002182	
Horizontal Header:		A24002 102	
Each header (manifold) comes complete with header valve for vacuand for EACH connection 1 x header valve, 1 x auxiliary valve & 1 x		& heater,	
,,,,,,,,	2 x drums	HMT-122	
	3 x drums	HMT-123	
	4 x drums	HMT-124	
Chlorine Manifold Y-Strainer (weight 2 kg) Carbon Steel Body, Monel Screen, Lead Gasket Sealed Cover Chlorine Manifold Filter (weight 20 kg)	3/4" NPT	RH-6786	
25,000 lb. tensile strength grey iron casting rated at 560 psi (38 bar) comes with removable filter cartridge. Acts as a filter and condensa		C-282	
-	·		
Heater for header mounting, 240V AC, 25W NB: Use RCD Safety		A24002479	
This is for all for 200, 500, 700 & 900 series Ton mount vacuu. Optional heater for header mounting, 24V AC, 25W c/w 240v transformation. Note: for second 24v heater add \$ 212 (max. 2 heaters per	ormer	PA55052460	
For extra ton units Power Supply: 2 x 24V60Va 240V Supply	ir dranoromnor).	PA55002460	
Heater for ton mounting drip leg, 24V AC, 25W, (75 x 50 pad)		84A24V	
Jniversal TON mounting Drip Leg c/w heater		PA-TUY-1	
Complete Dripleg assembly for 900 series Ton Mount Vacuum Regu	lator	VRH-999-500	
njection Systems:			
Withdrawable * PVC Injection lance, with 20mm hose tail, inc. SS va		PA07621807	
<u>Withdrawable</u> * PVC injection lance, with 25mm hose tail, inc. SS va Note: Suitable for maximum of 2 kg/h chlorine. Non Withdrawable PVC Injection/Diffuser tube c/w 1" BSPF	aive & nippie	PA07621808	
PVC valve & 25mm Hose Tail. <i>Note: Suitable for maximum of 2</i> Non Withdrawable PVC Injection/Diffuser tube c/w 1 1/2" BSPF	kg/h chlorine.	PA24921972	
PVC valve & 40mm Hose Tail. Note: Suitable for maximum of 1	0 kg/h chlorine.	PA24521971	
ndicators		DA04000400	
Auto vacuum change over Left/Right cylinder bank indicator, mounted in 175 x 125 PVC enclosure. Note: Requires auto cha	angeover value or extr	PA24002108	
High/Low vacuum indicator fitted to remote meter,	-	PA24002109	
mounted in 175 x 125 PVC enclosure. <i>Note: Requires remote Note: if both PA24002108 and 2109 are used together total pri</i>		/ \$435	
Special lubricant for O-Rings MOLYKOTE 100gm tube		FS 3452	
Twisted Spanner		HTS-1	
Vacuum Gauge 2-1/2" dia. Direct Mount with Diaphragm Protection		VGL-30	
Carbon Vent Trap see <i>picture p.14</i>		PA24002983	

hydro Gas Chlorinator Accessories

Flexible Tubing:

PE Tube

P-138-Y	3/8" OD X 1/4" ID Vacuum Tubing / Meter (2kg/hr) ONLY for older systems.
P-112-Y	1/2" OD X 3/8" ID Vacuum Tubing / Meter (5kg/hr) ONLY for older systems.
P-158/Y	5/8" OD X 1/2" ID Vacuum Tubing / Meter (10kg/hr) ONLY for older systems.

Kynar® Tube Fittings

BKF-64

BKF-64	Black Kynar Tube Connection. 1/4" X 3/8" Tube (2kg/hr)
DIZE 04	Disak Kupar Tuba 1/4" V 1/9" Tuba (Fire /br)

BKF-84 Black Kynar Tube. 1/4" X 1/2" Tube (5kg/hr)

BKF-108 Black Kynar Tube Connection. 1/2" X 5/8" Tube (10kg/hr)

BKT-6 Black Kynar Tube Union Tee 3/8" Tube (2kg/hr)
BKT-8 Black Kynar Tube Union Tee 1/2" Tube (5kg/hr)
BKT-10 Black Kynar Tube Union Tee 5/8" Tube (10kg/hr)

Alturnative (no longer used)


E.V.A. Chlorine vacuum tubing 12 x 8mm. *Note: price is per metre* A24001626 E.V.A. Chlorine vacuum tubing 17 x 12mm. *Note: price is per metre* A24001737

Note:

For over 50 years, **Kynar**® polyvinylidene fluoride (**PVDF**) resin, a specialty thermoplastic fluoropolymer, has been used in applications that require high strength and purity. Known for its high purity, Kynar® PVDF resins also provide chemical resistance to acids and bases, abrasion resistance, flame retardency, mechanical strength, impact resistance, thermal stability and ease of processing - making it the ideal choice for the development of highly durable and sustainable lightweight materials.










BKF-108

hydro Gas Chlorinator





1.8m FX-06 & 1.2m FX-04 Flexible connections for Drums & Cylinders, Tested.

A24002182 Adaptor for use with 1.8m A24002107 & 1.0m A24002264 Flexible connections











PA24002983 Carbon Vent Trap



15mm PVC Solvent Weld to 12 x 8 Tube 15mm PVC Solvent Weld to 17 x 12 Tube 15mm PVC Solvent Weld to 1/2" NPT

1/4"	NPT	O-Ring	to	12	Х	8	Tube
3/8"	NPT	O-Ring	to	12	Х	8	Tube
3/8"	NPT	O-Ring	to	17	Х	12	Tube
1/2"	NPT	O-Ring	to	17	Х	12	Tube

PA24002142 PA24001001 PA24022792

PA24001634 PA24001635 PA24001738 PA24022768