

# Peristaltic metering pump DULCO flex Control - DFYa

The peristaltic pump DULCO flex Control - DFYa combines the properties of top products from the ProMinent product range

ProMinent®



## Feed rate of 5.1 l/h to 410 l/h at up to 8 bar back pressure

The new metering pump DFYa, the big brother of the DFx, adds an intelligent peristaltic pump to the top capacity range of the ProMinent portfolio.

The new generation of peristaltic metering pumps is now controlled electronically. It meters without the need for a valve, with precision hitherto impossible. All the benefits of a peristaltic pump are retained, which is why seriously gaseous, high-viscosity, abrasive or shear-sensitive fluids, sometimes containing particles, can also be perfectly metered with the DFYa.

As with the DFx, hose replacement on the DFYa is also assisted by the pump. When the hose needs to be changed, the pump displays exact instructions for the steps to be followed and automatically moves into the correct positions for hose replacement. The different hose materials (NR, NBR, NBR-A, EPDM Hypalon) enable the DFYa to work with a very wide range of media to be metered.

The peristaltic pump DFYa is simple to operate from the intuitive user interface with 4 keys and the click wheel. The DFYa thus joins the remaining ProMinent product range of intelligent metering pumps, which all share the same menu structure and user interface.

## Your benefits

- Operation by contact, batch, manual, analogue or BUS control
- Adjustment of the metering rate directly in l/h or gph
- Connection to process control systems via a BUS interface, such as PROFIBUS®, Profinet or CANbus
- No problems with very gaseous media or air locks
- Simple, menu-guided hose change
- Reversible direction of rotation

## Field of application

- Mining
- Potable water and waste water industry
- Chemical industry
- Paper industry
- Food and beverage industry

All industrial applications, either as a stand-alone unit or integrated in a complete system.



# Peristaltic metering pump DULCO flex Control - DFYa

The peristaltic pump DULCO flex Control - DFYa combines the properties of top products from the ProMinent product range

## Technical Data

Type	Maximum back pressure bar	Pump capacity	Max. speed rpm	Suction lift m WC	Intake head m WC
08410	8	410 l/h ± 10 %	80	8	8
04410	4	410 l/h ± 10 %	80	8	8
02410	2	410 l/h ± 10 %	80	8	8

<b>Hose material:</b>	NR, NBR, EPDM, NBR-A, Hypalon
<b>Self-priming:</b>	Up to 8 m
<b>Rollers/shoes:</b>	Rollers
<b>Metering reproducibility:</b>	±2% with retracted hose after 500 revolutions
<b>Electrical connection:</b>	100 – 230 VAC ± 10 % 50/60 Hz
<b>Electrical power consumption:</b>	Max. 400 W
<b>Degree of protection:</b>	IP 55
<b>Weight:</b>	30 kg
<b>Permissible ambient temperature:</b>	0 ... 45 °C

### ■ SYDNEY OFFICE

Unit 4, 4 Narabang Way,  
BELROSE NSW 2085  
P 02 9450 0995  
F 02 9450 0996  
sales@prominentfluid.com.au

### ■ QUEENSLAND OFFICE

Unit 1, 68 Murdoch Circuit,  
ACACIA RIDGE QLD 4110  
P 07 3213 1900  
F 02 9450 0996  
pfcqld@prominentfluid.com.au

### ■ VICTORIA OFFICE

Unit 1/21-22 National Drive  
HALLAM VIC 3803  
P 03 8795 7430  
F 02 9450 0996  
pfcvic@prominentfluid.com.au

### ■ WESTERN AUSTRALIA OFFICE

Office 11, 34 Welshpool Road  
WELSHPOOL WA 6106  
pfcwa@prominentfluid.com.au