

Peristaltic pump DULCO flex Control - DFXa

A peristaltic pump that brings together the best qualities of ProMinent metering pumps

ProMinent®



Feed rate of 6 ml/h to 65 l/h at up to 7 bar back pressure

The new DULCO flex Control DFXa meters reliably and is simple to operate. It enhances the ProMinent product range with an intelligent peristaltic metering pump. ProMinent is making use of its decades-long experience in the metering pump sector to bring together the best of two worlds.

Valvefree metering with the accuracy of a diaphragm metering pump, with full use of the properties of a peristaltic pump.

The applications of this metering pump include strongly gaseous, high-viscosity, abrasive, shear-sensitive or chemically aggressive fluids.

The liquid end developed and patented by ProMinent makes quick and straightforward hose replacement possible with a unique exchange technique. The display provides the fitter with precise instructions about the steps to be completed when replacing the hose. The high-performance hoses used guarantee exceptional chemical resistance and a long service life.

The order information required for replacement of the hose can be found on the pump's operating menu.

The intuitive user interface with click wheel ensures the simple operation of the peristaltic pump.

A brushless direct current motor forms the heart of the DULCO flex Control DFXa. Its ingenious control provides for precise metering and reduced pump capacity with continuous metering up to 6 ml/h. Moreover, the new peristaltic metering pump is IoT-enabled, meaning that it is fully networkable and can be connected to the DULCONneX platform especially developed by ProMinent, which enables it to work even smarter.

Your benefits

- Adjustment of the metering rate directly in l/h or gph
- Simple hose change
- No problems with very gaseous media or air locks
- Suitable for viscosities of up to 200,000 mPas
- Sole contact with media in the hose
- Many different control options, such as using an analogue 0/4-20 mA signal, contact controller, timer or via process control systems

Field of application

- Potable water and waste water treatment
- Food and beverage industry
- Paper industry
- Chemical industry
- Chemical distributors
- Electroplating
- Swimming pools
- All industrial applications, either as a stand-alone unit or integrated in a complete system



Peristaltic pump DULCO flex Control - DFXa

A peristaltic pump that brings together the best qualities of ProMinent metering pumps

Technical Data

Type	Maximum back pressure	Pump capacity	Max. speed rpm	Connector size	Suction lift	Intake head	Shipping weight
	bar		rpm	o Ø x i Ø	m WC	m WC	kg
0518	5	6 ml/h – 18 l/h	100	12 x 9	9	9	5.8
0530	5	10 ml/h – 30 l/h	100	12 x 9	9	9	5.8
0730	7	10 ml/h – 30 l/h	100	12 x 9	9	9	5.8
0565	5	22 ml/h – 65 l/h	100	12 x 9	9	9	5.8

Hose material:	Thermoplastic vulcanisate (TPV), polyurethane (PUR)
Hose connectors:	PVDF/PTFE
Metering reproducibility:	±2% with retracted hose (after approx. 200 revolutions)
Electrical connection:	100 - 230 V ±10%, 50/60 Hz
Nominal power:	approx. 50 W
Degree of protection:	IP 66, NEMA 4X Indoor
Permissible ambient temperature:	0 ... 45 °C

All data refers to water at 20 °C

■ SYDNEY OFFICE

Unit 4, 4 Narabang Way,
BELROSE NSW 2085
P 02 9450 0995
F 02 9450 0996
sales@prominentfluid.com.au

■ QUEENSLAND OFFICE

Unit 1, 68 Murdoch Circuit,
ACACIA RIDGE QLD 4110
P 07 3213 1900
F 02 9450 0996
pfcqld@prominentfluid.com.au

■ VICTORIA OFFICE

Unit 1/21-22 National Drive
HALLAM VIC 3803
P 03 8795 7430
F 02 9450 0996
pfcvic@prominentfluid.com.au

■ WESTERN AUSTRALIA OFFICE

Office 11, 34 Welshpool Road
WELSHPOOL WA 6106
pfcwa@prominentfluid.com.au