

ProGuard Chlorine Shut Off PNEUMATIC

The ProMinent® ProGuard auto shut off system provides for fast acting, fail safe emergency closure of either drum or cylinder valves

ProMinent®



System Features

- Manual operation.
- Integration with leak detectors.
- Pneumatic operation with electronic control.
- Connection to either process air or stand alone bottle air or N₂.
- Battery backup 8 hours or greater.
- Fail safe design.
- Single drum / bottle or multiple operation.
- Supplied with new equipment or retro fitted to existing units.

System Operation

The pneumatic cylinder oscillates to close the valve.

The System activates when:

- Alarm contact is activated
- Low battery life is sensed
- Low air pressure is sensed in the actuation system
- Manually initiated

■ SYDNEY OFFICE

Unit 4, 4 Narabang Way,
BELROSE NSW 2085
P 02 9450 0995
F 02 9450 0996
sales@prominentfluid.com.au

■ QUEENSLAND OFFICE

Unit 1, 68 Murdoch Circuit,
ACACIA RIDGE QLD 4110
P 07 3213 1900
F 02 9450 0996
pfcqld@prominentfluid.com.au

■ VICTORIA OFFICE

Unit 1/21-22 National Drive
HALLAM VIC 3803
P 03 8795 7430
F 02 9450 0996
pfcvic@prominentfluid.com.au

■ WESTERN AUSTRALIA OFFICE

Office 11, 34 Welshpool Road
WELSHPOOL WA 6106
pfcwa@prominentfluid.com.au

www.prominentfluid.com.au